

SAFETY DATA SHEET

1. Identification

Product number 1000001358
Product identifier **CHAIN & CABLE LUBRICANT**
Revision date 06-16-2015
Company information JCC CHEMICAL CORP
8821-31 NW 102 ST.
MIAMI, FL 33178 United States
Company phone General Assistance 787-633-2915
Emergency telephone US 1-866-836-8855
Emergency telephone outside US 1-952-852-4646
Version # 02
Supersedes date 06-11-2015
Recommended use Lubricant
Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1
Health hazards Sensitization, skin Category 1B
Germ cell mutagenicity Category 1B
Carcinogenicity Category 1B
Specific target organ toxicity, repeated exposure Category 1
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements



Signal word Danger
Hazard statement Extremely flammable aerosol. May cause an allergic skin reaction. May cause genetic defects. May cause cancer. Causes damage to organs through prolonged or repeated exposure.
Precautionary statement
Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.
Response If on skin: Wash with plenty of water. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Storage Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal Not available.
Hazard(s) not otherwise classified (HNOC) None known.
Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Propane		74-98-6	10 - 20
Mineral Spirits		8052-41-3	2.5 - 10
Cocoyl Diethanolamide		68603-42-9	1 - 2.5
Solvent Naphtha (Petroleum), Medium Aliphatic		64742-88-7	1 - 2.5
Diethanolamine		111-42-2	0.1 - 1
Other components below reportable levels			60 - 80

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Wash off with soap and plenty of water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Launder contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Dermatitis. Rash. Direct contact with eyes may cause temporary irritation. May cause an allergic skin reaction. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	--

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Never return spills in original containers for re-use.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage**Precautions for safe handling**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not re-use empty containers. Do not breathe gas. Do not get in eyes, on skin, on clothing. Avoid contact with eyes, skin, and clothing. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
Mineral Spirits (CAS 8052-41-3)	PEL	2900 mg/m3
Propane (CAS 74-98-6)	PEL	500 ppm
		1800 mg/m3
		1000 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Diethanolamine (CAS 111-42-2)	TWA	1 mg/m3	Inhalable fraction and vapor.
Mineral Spirits (CAS 8052-41-3)	TWA	100 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Diethanolamine (CAS 111-42-2)	TWA	15 mg/m3
Mineral Spirits (CAS 8052-41-3)	Ceiling	3 ppm
		1800 mg/m3
		350 mg/m3
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines**US - California OELs: Skin designation**

Diethanolamine (CAS 111-42-2) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Diethanolamine (CAS 111-42-2) Can be absorbed through the skin.

Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Individual protection measures, such as personal protective equipment	
Eye/face protection	If contact is likely, safety glasses with side shields are recommended.
Hand protection	Wear appropriate chemical resistant gloves.
Skin protection	
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Skin protection	
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance	Viscous.
Physical state	Gas.
Form	Aerosol.
Color	Black.
Odor	Solvent.
Odor threshold	Not available.
pH	Not applicable estimated
Melting point/freezing point	Not available.
Initial boiling point and boiling range	-43.78 °F (-42.1 °C) estimated
Flash point	-156.0 °F (-104.4 °C) Propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	2.2 % estimated
Flammability limit - upper (%)	9.5 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	80 - 90 psig @ 70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	50 - 150 cP
Other information	
Specific gravity	0.89 - 0.905 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use. Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Fluorine. Chlorine. Nitrates.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Not available.
Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation.
Skin contact	Harmful in contact with skin. May cause an allergic skin reaction.
Eye contact	Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death. Dermatitis. Rash. Direct contact with eyes may cause temporary irritation. May cause an allergic skin reaction.

Information on toxicological effects

Acute toxicity Harmful in contact with skin. May cause an allergic skin reaction.

Product	Species	Test Results
TERAND CHAIN & CABLE LUBRICANT (CAS Mixture)		
Acute		
<i>Dermal</i>		
LD50	Rat	2535 mg/kg
<i>Inhalation</i>		
LC50	Rat	3 mg/l/4h
<i>Oral</i>		
LD50	Rat	
Components	Species	Test Results
Calcium Sulfonate, Particulate (CAS 61789-86-4)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
	Rat	> 2000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	> 1.9 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	10000 - 20000 mg/kg
Diethanolamine (CAS 111-42-2)		
Acute		
<i>Oral</i>		
LD50	Rat	1100 mg/kg
Propane (CAS 74-98-6)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l

Components	Species	Test Results
		658 mg/l/4h
Solvent Naphtha (Petroleum), Medium Aliphatic (CAS 64742-88-7)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg > 2000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Cat	> 6.4 mg/l, 6 Hours
	Rat	> 7.5 mg/l, 6 Hours > 4.3 mg/l, 4 Hours > 0.1 mg/l, 8 Hours
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	May cause genetic defects.
Carcinogenicity	May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Cocoyl Diethanolamide (CAS 68603-42-9)	2B Possibly carcinogenic to humans.
Diethanolamine (CAS 111-42-2)	2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Respiratory system. Skin. Kidneys. Central nervous system. Eyes. Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not an aspiration hazard. Not likely, due to the form of the product.
Chronic effects	Prolonged exposure may cause chronic effects. Causes damage to organs through prolonged or repeated exposure.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Product	Species	Test Results
TERAND CHAIN & CABLE LUBRICANT (CAS Mixture)		
Aquatic		
Algae	IC50	Algae 2975 mg/L, 72 Hours
Crustacea	EC50	Daphnia 1001 mg/L, 48 Hours
Fish	LC50	Fish 209 mg/L, 96 Hours
Components	Species	Test Results
Diethanolamine (CAS 111-42-2)		
Aquatic		
Algae	IC50	Algae 7.8 mg/L, 72 Hours
Crustacea	EC50	Daphnia 55 mg/L, 48 Hours
Fish	LC50	Fathead minnow (Pimephales promelas) 100 mg/l, 96 hours

Components	Species	Test Results
Solvent Naphtha (Petroleum), Medium Aliphatic (CAS 64742-88-7)		
Aquatic		
Crustacea	EC50 Daphnia	100.0001 mg/L, 48 Hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Diethanolamine	-1.43
Mineral Spirits	3.16 - 7.15
Propane	2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft Allowed.

Cargo aircraft only Allowed.

Packaging Exceptions LTD QTY

IMDG

UN number UN1950

UN proper shipping name AEROSOLS

Transport hazard class(es)

Class 2.1

Subsidiary risk -

Label(s) 2.1

Packing group Not applicable.

Environmental hazards

Marine pollutant No.

EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions LTD QTY

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Diethanolamine (CAS 111-42-2) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - No
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1,2,4-Trimethyl Benzene	95-63-6	0.1 - 1
Diethanolamine	111-42-2	0.1 - 1
Ethyl Benzene	100-41-4	0.01 - 0.1

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Diethanolamine (CAS 111-42-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations**US. Massachusetts RTK - Substance List**

Diethanolamine (CAS 111-42-2)

Mineral Spirits (CAS 8052-41-3)

Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Diethanolamine (CAS 111-42-2)

Mineral Spirits (CAS 8052-41-3)

Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Diethanolamine (CAS 111-42-2)

Mineral Spirits (CAS 8052-41-3)

Propane (CAS 74-98-6)

US. Rhode Island RTK

Diethanolamine (CAS 111-42-2)

Propane (CAS 74-98-6)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Cocoyl Diethanolamide (CAS 68603-42-9) Listed: June 22, 2012

Diethanolamine (CAS 111-42-2) Listed: June 22, 2012

Ethyl Benzene (CAS 100-41-4) Listed: June 11, 2004

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	05-27-2015
Revision date	06-16-2015
Version #	02
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision Information	Product and Company Identification: Alternate Trade Names